

**TITLE OF THE INVENTION**

**METHOD AND APPARATUS FOR ALARMING ON OCCURRENCE OF CELL  
SECESSION OF A MOBILE STATION IN A MOBILE COMMUNICATION SYSTEM**

**PRIORITY**

This application makes reference to, incorporates the same herein, and claims all benefits accruing under 35 U.S.C. § 119 from an application entitled "Method for Alarming Cell Secession in Mobile Station of Mobile Telecommunication System" earlier filed in the Korean Industrial Property Office on May 24, 2000 and there duly assigned Serial No. 2000-28079.

**BACKGROUND OF THE INVENTION**

**Field of the Invention**

The present invention relates generally to a radio mobile communication system, and in particular, to a method for generating, when a subscriber secedes from a base station transceiver subsystem (BTS), an alarm signal for informing a subscriber's terminal or a mobile station, of the secession.

## Description of the Related Art

1  
2 In a code division multiple access (CDMA) mobile communication system, a mobile station  
3 measures the strength of a signal transmitted from a BTS and displays received signal strength  
4 indication (RSSI) on a liquid crystal display (LCD) to enable the terminal user to observe the  
5 receiving sensitivity on the user's location. Further, the mobile station controls transmission power  
in inverse proportion to a level of the measured RSSI.

6  
7 For example, the mobile station can display the level of the RSSI on the LCD using vertical  
8 rods, so that the subscriber can be visibly aware of the level of the RSSI at the sight of the rod  
9 indication. However, during a call, the user may have a difficulty in checking the rod indication  
10 representative of the level of the RSSI, so that the user may not be able address a situation where  
11 the level of the RSSI is lowered which can cause a decrease in the call sensitivity or a call drop, the  
12 call drop typically being undesirable the user.

13 U.S. Patent No. 4,996,715 to Marui *et al.* entitled *Radio Telephone Apparatus* disclose a  
14 radio telephone apparatus for use in a cellular mobile telephone system including means for  
15 alarming at least a user operating the apparatus in response to a drop in signal strength of radio  
16 frequency signals received over an established communication channel when the apparatus  
17 approaches a boundary of service area in a cellular mobile telephone system. The signal strength is

1 repetitively checked to determine if it has fallen below a first predetermined signal strength value.  
2 When the signal strength falls to or below a second predetermined signal strength value, the radio  
3 telephone apparatus causes a disconnection of the telephone link and returns the apparatus to a  
4 standby mode.

5 U.S. Patent No. 5,105,458 to Takenaka entitled *Mobile Telephone System Having Message*  
6 *Recording Mode During Failures* discloses a mobile telephone system, whereby a base station  
7 establishes a radio link to a mobile station and a connection to a switched telephone network when  
8 the mobile station is in communication with a network-side station. The base station monitors signals  
9 from the mobile station over the radio link. If the base station detects that the radio link is failing  
10 during a communication, an announcement is transmitted to the network-side station.

11 U.S. Patent No. 5,134,708 to Marui *et al.* entitled *Radio Telephone Apparatus* disclose a  
12 radio telephone apparatus for use in a cellular mobile telephone system that includes an alarm to  
13 inform a user of a drop in signal strength of radio frequency signals received over an established  
14 communication link. Further, the mobile unit detects the presence or strength of a tone signal  
15 modulated on at least one of the received radio signals. The mobile unit disconnects the telephone  
16 link and returns to a standby mode if the tone signal is lost or becomes too weak.

1 U.S. Patent No. 5,671,218 to I *et al.* entitled *Controlling Power And Access Of Wireless*  
2 *Devices To Base Stations Which Use Code Division Multiple Access* disclose that data signals to be  
3 transmitted from a plurality of wireless devices are spread across a common bandwidth. The data  
4 signals are received by a base station as a composite spread signal. The base station partially  
5 despreads the composite spread signal with unique codes to extract data signals from individual  
6 wireless devices. The data rate and quality of service requirements for each wireless device are used  
7 to calculate a power factor and a control signal is sent to control the power from a particular wireless  
8 device. In addition, a probability of transmission value is calculated based on an equivalent current  
9 load value and an equivalent population value. The probability of transmission value determines  
10 whether a particular wireless device is allowed access to an uplink frequency channel.

11 U.S. Patent No. 5,684,790 to Hirasawa entitled *Mobile Communication System* discloses a  
12 mobile communication system that can preliminarily inform a user of the possibility of an  
13 occurrence of interruption of a call, which is peculiar to the system of the TDMA type. In this  
14 mobile communication system, a CPU measures a received level of speech quality by detecting data  
15 representing speech quality in an SACCH frame on the basis of a result of analysis of a received  
16 frame by means of a receiving portion. In the case where the received level is less than a  
17 predetermined value, a counting portion is caused to start counting. If the received level is low in  
18 the case of the next SACCH frame, the count is incremented. When the count reaches a

1 predetermined value, a speaker serving as an alarming means is operated so as to produce a warning  
2 tone, so that a warning is given to a person who is currently using the system.

3 U.S. Patent No. 5,799,244 to Matsumoto entitled *Digital Mobile Unit Having A Function Of*  
4 *Issuing A Tone Level Controllable Input Signal Degradation Alarm And A Method Thereof*  
5 discloses that in order to adaptively control a level of an alarm which warns of imminent or  
6 impending communication interruption, an error information signal and data frame energy, which  
7 are both derived during the decoding of an incoming signal, are used. If the incoming signal is  
8 deteriorated to an extent that communication interruption is imminent, an alarm signal is issued and  
9 superimposed on a voice signal. The level of the alarm signal is controlled in accordance with the  
10 detected frame energy.

11 U.S. Patent No. 5,859,838 to Soliman entitled *Load Monitoring And Management In A*  
12 *CDMA Wireless Communication System* discloses a system and method for monitoring and  
13 managing the loading conditions in a CDMA wireless communication system. The system includes  
14 a load monitoring device, such as a CDMA mobile station, connected to a data logging and  
15 processing device, such as a diagnostic monitor. The monitoring device is placed within the service  
16 area of a base station. The monitoring device periodically initiates a call, is assigned to a traffic  
17 channel normally, and logs a power control parameter such as a mobile station transmit power or the  
18 number of closed-loop power control commands received per unit time. From this information, the

1 load monitoring device can infer the real-time traffic loading conditions of the base station. If the  
2 loading of the system exceeds a predetermined threshold, an alarm may be sent to the system  
3 management center in order to take some action to limit additional loading on the base station.

#### 4 SUMMARY OF THE INVENTION

5 It is, therefore, an object of the present invention to provide a method for alarming on  
6 occurrence of cell secession when a subscriber's terminal secedes from a cell presently in service,  
7 by using the power control or handoff function to call to the subscriber's attention the occurrence  
8 of cell secession, in a mobile communication system.

9 To achieve the above and other objects of the present invention, there is provided a method  
10 for alarming on occurrence of cell secession of a mobile station in a mobile communication system.  
11 In the method, a base station transceiver subsystem (BTS) receives power-related information  
12 transmitted from each mobile station, and analyzes the power-related information to determine  
13 whether each mobile station has seceded from a corresponding cell. The BTS transmits cell secession  
14 alarm information to a cell-seceded mobile station to enable the cell-seceded mobile station to  
15 perform a cell secession alarm operation.

16 Preferably, to detect the occurrence of cell secession of the mobile station, the BTS

523  
A3  
1 determines whether a power level of the mobile station is less than or equal to a predetermined  
reference power level. Also, preferably, the BTS transmits a predetermined tone control message  
3 as the cell secession information when secession occurs over a forward traffic channel in the mobile  
4 communication system.

### BRIEF DESCRIPTION OF THE DRAWINGS

6 A more complete appreciation of the invention, and many of the attendant advantages  
7 thereof, will be readily apparent as the same becomes better understood by reference to the following  
8 detailed description when considered in conjunction with the accompanying drawings in which like  
9 reference symbols indicate the same or similar components, wherein:

10 FIG. 1 is a diagram illustrating a network structure for explaining the concept of a private  
11 mobile communication service to which the present invention is applicable;

523  
A3  
12 FIG. 2 is a flow chart illustrating a procedure for alarming on occurrence of cell secession  
13 of a mobile station in a mobile communication system according to an embodiment of the present  
14 invention; and

15 FIG. 3 is a diagram illustrating exemplary types of messages on a forward traffic channel in  
16 the mobile communication system to which the present invention is applied.

34B  
AS

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

2 Preferred embodiments of the present invention will be described herein below with  
3 reference to the accompanying drawings of FIGS. 1 through 3.

4 The present invention is preferably applied to a private radio switching system. In general,  
5 a mobile communication system performs cell mapping so as to cover the entire region of a nation,  
6 for example. Therefore, when a mobile station located in a specific cell moves out of, or secedes  
7 from, the specific cell, a handoff occurs to a target cell to which the mobile station is moving.

8 However, the private radio switching system is generally structured such that a call is dropped when  
9 a private mobile station moves out of the cell coverage. Therefore, it is preferable to apply the  
10 methods and apparatus of the present invention for alarming upon occurrence of cell secession of  
11 the mobile station in the private radio switching system.

12 FIG. 1 illustrates a network structure for explaining the concept of a private mobile  
13 communication system to which the present invention is applicable. Referring now to FIG. 1, FIG.  
14 1 illustrates a public/private common radio communication system 1. Referring to FIG. 1, the  
15 public/private radio communication system 1 includes a public/private common cell 14, which is a  
16 public/private common communication service area, and a public/private communication service unit  
17 12. Preferably, the public/private common cell 14 is set so as to provide a communication service



54B  
RC  
1 to a specific group as a private mobile communication system 1A. For example, when a certain  
2 company or organization uses, or occupies, one building, the area belonging to the building can be  
3 defined as the public/private common cell 14.  
4

5 Continuing with reference to FIG. 1, the public/private common cell 14 is preferably defined  
6 by mutual agreement with the public mobile communication service provider. In this regard, this  
7 is to have a private base station transceiver subsystem (BTS)  $8_k$  in the public/private common cell  
8 14 to be recognized as a private BTS (pBTS) from the viewpoint of a public mobile communication  
9 system 1B. In the following description, the private BTS  $8_k$  will be referred to as "pBTS", in order  
10 to distinguish the private BTS  $8_k$  in the public/private common cell 14 from the base station  
11 transceiver subsystems (BTSSs) belonging to the public mobile communication system 1B, namely,  
12 the BTSSs  $6_1$ - $6_k$  (BTS1 to BTSSk) to BTS  $8_1$  (BTS1) shown in FIG. 1, for example. The pBTS  $8_k$ ,  
13 together with a mobile station (MS) 24 in the public/private common cell 14, forms a radio  
14 communication path, to perform a function of managing radio resources, and is connected to a base  
15 station controller (BSC)  $4_m$  (BSCn) of the public mobile communication system 1B through the  
16 public/private communication service unit 12. The public/private communication service unit 12 is  
17 connected to BSC  $4_m$  (BSCn), public switched telephone network/integrated services digital network  
18 (PSTN/ISDN) 16, and internet protocol (IP) network 18.

19 Also, the public/private communication service unit 12 can optionally provide the public

1 mobile communication service and the private mobile communication service to any of the mobile  
2 stations (MS) 24, 24a to 24n, such as to the MS 24, in the public/private common cell 14. Moreover,  
3 if a mobile station, such as the MS 24, is registered in the public/private communication service unit  
4 12 to receive the private mobile communication service, the MS 24 can receive not only the public  
5 mobile communication service but also the private mobile communication service, as well.  
6 However, if a mobile station, such as the MS 24, is not registered in the public/private  
7 communication service unit 12, the MS 24 can receive only the public mobile communication  
8 service. In addition, the public/private communication service unit 12 can perform a wire  
9 communication service with the PSTN/ISDN 16 and the IP network 18.

10 Continuing with reference to FIG. 1, the public mobile communication network or system  
11 1B is commonly part of a public land mobile network (PLMN). As illustrated in FIG. 1, the public  
12 land mobile communication network includes a plurality of mobile switching centers (MSCs) 2<sub>1</sub>-  
13 2<sub>n</sub>, (MSC1 to MSCn), a plurality of base station controllers (BSCs) 4<sub>1</sub>-4<sub>m</sub> (BSC1 to BSCn), a  
14 plurality of base station transceiver subsystems (BTSs) 6<sub>1</sub>-6<sub>k</sub> (BTS1 to BTSk) to 8<sub>1</sub>-8<sub>k</sub> (BTS1 to  
15 BTSk), a plurality of mobile stations (MSs) 20, 22 and 24, 24a to 24n and a home location  
16 register/visitor location register (HLR/VLR) 10. Each of the MSCs 2<sub>1</sub>-2<sub>n</sub> (MSC1 to MSCn) is  
17 connected to its associated corresponding one of BSCs 4<sub>1</sub>-4<sub>m</sub>, (BSC1-BSCn) and each of the BSCs  
18 4<sub>1</sub>-4<sub>m</sub> (BSC1-BSCn) is respectively connected to its associated corresponding BTSs 6<sub>1</sub>-6<sub>k</sub> (BTS1-  
19 BTSk) to 8<sub>1</sub>-8<sub>k</sub> (BTS1 - BTSk). In particular, the pBTS 8<sub>k</sub> is one of the BTSs 8<sub>1</sub>-8<sub>k</sub> (BTS1 to BTSk)

1 connected to the BSC 4<sub>m</sub> (BSC<sub>n</sub>) of the public mobile communication system 1B according to an  
2 embodiment of the present invention.

3 Continuing with reference to FIG.1, the MSCs 2<sub>1</sub>-2<sub>n</sub> (MSC1- MSC<sub>n</sub>) each respectively  
4 control the connection between the BSCs 4<sub>1</sub>-4<sub>m</sub> (BSC1-BSC<sub>n</sub>) respectively connected thereto and  
5 the PSTN/ISDN 16 or another MSC in the public mobile communication network or system 1 B.  
6 The BSCs 4<sub>1</sub>-4<sub>m</sub> (BSC1 to BSC<sub>n</sub>) each perform radio link control and handoff functions, and the  
7 BTSs 6<sub>1</sub>-6<sub>k</sub> (BTS1 to BTS<sub>k</sub>) to 8<sub>1</sub>-8<sub>k</sub> (BTS1 to BTS<sub>k</sub>) perform the functions of forming radio  
8 communication paths to the respective MSs 20, 22 and 24, 24a to 24n belonging to their  
9 communication service area, i.e., their cell area and managing the radio resources. In the  
10 HLR/VLR 10, the home location register (HLR) has a subscriber location registration function  
11 and a database function for storing subscriber information, and the visitor location register (VLR)  
12 has a database function for temporarily storing information about the MS existing in the cell  
13 managed by a corresponding one of the MSCs 2<sub>1</sub>-2<sub>n</sub> (MSC1-MSC<sub>n</sub>). If the MS moves to a cell  
14 managed by another MSC, the corresponding information stored in the VLR of the HCR/VCR 10  
15 is deleted.

16 In the above described system, such as illustrated in FIG. 1, radio communication service  
17 typically will be provided free of charge between the mobile stations MS 24, 24a to 24n in the  
18 public/private common cell 14 of the pBTS 8<sub>k</sub> which is the BTS registered in the public/private

1 communication service unit 12, i.e., the mobile stations registered in the private radio network.  
2 Therefore, during a call between the mobile stations registered in the private network within the  
3 public/private common cell 14, if a corresponding mobile station secedes from the public/private  
4 common cell 14, the call will be dropped or the mobile station will use another BTS so that the  
5 subscriber typically would be charged for the call. In this case, it is preferable to apply the methods  
6 and apparatus for alarming upon occurrence cell secession of the mobile station according to the  
7 present invention.

8 Continuing with reference to FIG. 2, a detailed description will be made of an operation  
9 according to the methods and apparatus of the present invention. FIG. 2 illustrates a procedure for  
10 alarming upon occurrence of cell secession of a mobile station in a mobile communication system  
11 according to the present invention. A CDMA system performs very accurate power control so that  
12 a signal from a mobile station should be received at a BTS at the least signal-to-noise ratio (SNR),  
13 in order to maximize the capacity. The present invention desirably utilizes this power control  
14 function.

15 Each mobile station transmits a radio frequency (RF) signal for a new channel assignment  
16 request, and the RF signal includes data indicating a power level detected by the mobile station. Each  
17 mobile station periodically samples the power level transmitted from a corresponding BTS and then  
18 transmits the sampled power level back to the BTS. The BTS then receives the sampled power level

1 transmitted from each mobile station and analyzes a variation of the power level of the  
2 corresponding mobile station. Such an operation is performed for the power control and handoff of  
3 each mobile station. An operation according to the methods and apparatus of the present invention  
4 is performed by analyzing the information about the power level provided from the mobile station.

5 Referring now to FIG. 2, the process starts at step S20A, and a corresponding BTS receives  
6 a power control parameter of a mobile station from a corresponding BSC in step S20. Thereafter,  
7 in step S22, the corresponding BTS receives information about the received power level from the  
8 mobile station. The mobile station measures received power from the corresponding BTS and  
9 reports this information to the corresponding BTS through a "power measurement report message"  
10 or an "erasure indicator bit" which is inserted in every frame at a predetermined time. Accordingly,  
11 in step S22, the corresponding BTS receives information about the received power level from the  
12 corresponding mobile station, and then the corresponding BTS detects information about the frame  
13 quality from the received information in step S24. That is, upon receipt of the power measurement  
14 report message or the "erasure indicator bit", the corresponding BTS determines, such as by  
15 calculating, a forward frame error rate (FER) from an "error detected" field corresponding to the  
16 "erasure indicator bit" and a "power measure frame" field included in the received power  
17 measurement report message.

18 Continuing with reference to FIG. 2, the process proceeds to step S26, and , in step S26, the

1 corresponding BTS compares the frame quality with the power control parameter received from the  
2 corresponding BSC to monitor cell secession of the corresponding mobile station. That is, the mobile  
3 communication system compares the calculated, or determined, FER with a power control  
4 parameter value of the mobile communication system and predicts, or determines, a power level of  
5 the corresponding mobile station. When the power level of the corresponding mobile station  
6 decreases below a predetermined reference power level, the mobile communication system considers  
7 that the corresponding mobile station has seceded from the cell. Thus, in order to guarantee the  
8 reliability, the predetermined reference power level is set to a value which is slightly larger than a  
9 pilot power corresponding to the complete switching to the BTS, thereby to prevent generating alarm  
10 information due to erroneous information.

11  
12 The process then proceeds to step S28 in FIG. 2 and, in step S28, cell secession alarm  
13 information is transmitted to the corresponding mobile station, when cell secession is expected or  
14 upon occurrence of cell secession. That is, when it is considered that the corresponding mobile  
15 station has seceded from the cell, the mobile communication system transmits an alarm signal on  
16 a forward traffic channel in the mobile communication system, such as to a vocoder through an air  
17 interface. The signal transmitted over the forward traffic channel is transmitted to the corresponding  
18 mobile station to inform the subscriber in service of the present status that the mobile station is  
19 seceding from the cell. This alarm information is transmitted to the mobile station by setting a "flash-  
20 with-information message" or an "alert-with-information message" on the forward traffic channel.

1 Upon receipt of such message, the corresponding mobile station generates an alarm tone in step S29,  
2 and the process then proceeds to end at step S30. Accordingly, a subscriber at the corresponding  
3 mobile station can take a proper preliminary action.

4 Referring now to FIG. 3, FIG. 3 illustrates exemplary types of messages on the forward  
5 traffic channel in the mobile communication system over which the cell secession alarm information  
6 is transmitted, such as in the case where the method and apparatus of the present invention are  
7 applied to an IS-95 mobile communication system, for example, IS-95 being a CDMA "Mobile  
8 Station-Base Station Compatibility Standard for Dual Mode Wideband Spread Spectrum Cellular  
9 System". FIG. 3 illustrates various message names together with a corresponding message type and  
10 a corresponding meaning of a message (MSG) for a corresponding message in tabular form as can  
11 be implemented in the mobile communication system of FIG. 1, for example. In an embodiment of  
12 the present invention, for example, the alarm information is transmitted by setting a proper parameter  
13 to the "flash-with-information message" or the "alert-with-information message" on the forward  
14 traffic channel in the mobile communication system, as shown in FIG. 3.

15 Further, for example, when the process illustrated shown in FIG. 2 is applied to the private  
16 radio mobile communication system 1A of FIG. 1, for example, the corresponding BTS of the  
17 corresponding private radio mobile communication system 1A, such as PBTS 8<sub>k</sub> first performs an  
18 operation of determining whether the corresponding mobile station, such as MS24, is registered to

1 be able to use the private mobile communication service and whether an extension call is performed  
2 between registered subscribers, such as between registered mobile stations. When the call is an  
3 extension call between the registered subscribers, the cell secession alarm operation and process  
4 shown in FIG. 2 is performed. Otherwise, when the call is not an extension call between the  
5 registered subscribers, a handoff occurs to a neighbor BTS, such as BTS8<sub>1</sub>, upon detection of  
6 occurrence or expected occurrence of the cell secession.

7 As described above, a radio mobile communication system of the present invention generates  
8 an alarm signal to the mobile station when the subscriber's terminal, or mobile station, secedes from  
9 the designated cell during a call. In this manner, it is possible to alarm upon occurrence of or  
10 expected occurrence of cell secession before the call is dropped, when the subscriber is moving out  
11 of the service area (i.e., a specific BTS or a specific cell), thereby preventing an abrupt call drop.  
12 Such a function is typically more effective when applied to an in-building communication service  
13 system rather than to a general CDMA system, although the present invention can be applied to a  
14 general CDMA system.

15 In addition, as described above, the present invention advantageously does not necessarily  
16 use a dual tone multi-frequency (DTMF) sender resource of a time switch when transmitting the  
17 alarm signal. In general, the system to which the present invention is applicable typically has limited  
18 DTMF resources. Therefore, when one mobile station continuously occupies the DTMF resource,



1 typically other mobile stations cannot receive the DTMF service. Accordingly, the present invention  
2 receives a power-related message from the corresponding mobile station, analyzes the received  
3 message and transmits a tone control message over a forward traffic channel of the mobile  
4 communication system, thereby to advantageously save the common resources, such as DTMF  
5 resources, of the mobile communication system.

6 While the method and apparatus of the present invention has been shown and described with  
7 reference to a certain preferred embodiments, the methods and apparatus of the present invention  
8 should not be construed in a limiting sense. For example, although the present invention has been  
9 described with reference to an in-building private BTS, the methods and apparatus of the present  
10 invention can also be applied to a general CDMA system. That is, if the power level becomes too  
11 low to maintain the call and there is no neighbor BTS or no available channel, even though there is  
12 a neighbor BTS, the mobile communication system generates an alarm signal for the subscriber so  
13 that the subscriber may prepare for the call drop.

14 While there have been illustrated and described what are considered to be preferred  
15 embodiments of the present invention, it will be understood by those skilled in the art that various  
16 changes and modifications may be made, and equivalents may be substituted for elements thereof  
17 without departing from the true scope of the present invention. In addition, many modifications may  
18 be made to adapt a particular situation to the teaching of the present invention without departing

[illegible]